Forklift Seat Belt

Seat Belt for Forklifts - This guideline reason is to be able to explain the Regulation requirements for the use of driver restraints or seatbelts on forklifts. It is the employers' responsibility to ensure that every machine, piece of equipment and tool within the workplace is chosen and used properly and worked in accordance with the manufacturer's directions.

In regards to their design, maintenance, inspection, fabrication and use Rough Terrain forklifts have to meet the regulations of ANSI Standard ASME B56.6-1992.

Mobile machines like for example side boom tractors along with a Rollover Protective Structure (ROPS), should contain seat belts that meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile machine has seat belts required by law, the driver and subsequent passengers ought to make certain they use the belts whenever the motor vehicle is in motion or engaged in operation since this could cause the machinery to become unsteady and therefore, not safe.

If a seat belt or different driver restraint is needed on a forklift.

The seat belt requirements while working a forklift depend on various factors. Whether the forklift is equipped with a Rollover Protective Structure, the type of forklift itself and the year the forklift was manufactured all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

Referring to an operator restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to aid the operator in reducing the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device can include a seat belt, even if a seat belt is not essentially a part of such machine or system.