Industrial Jibs

Industrial Jib - The lift truck jib will allow a worker to transfer their very heavy heaps overtop of obstacles or obstructions onto roofs, elevated platforms, and even decks. They could be used to reach the second or third level building platforms to be able to distribute or pick up loads at places which are still under construction. Fork truck jibs are actually utilized in order to unload trucks and flatbed trailers, to suspend trusses and laminate wood. Jibs are also typically used for reaching over scaffolding intended for masonry work.

Each jib boom forklift attachment is made with a pair of swivel hooks. One hook could be manually fixed to any position on the boom's underside and the second hook is fixed at the end of the jib. This allows the person operating it to be able to lift whichever load which has two hook points. Depending upon the dimensions of the model, every hook is rated at either four thousand or six thousand lbs. It is possible to make use of either one hook or even two to be able to carry a load. The individual operating it must be certain that the total weight of the jib and the load doesn't go over the rated capacity of the jib as shown on the load chart for that retracted or extended position.

Jib attachments are made to be able to be utilized on industrial lift trucks, extendable-reach lift trucks, and even on rough terrain straight-mast lift trucks. Forklift jib cranes install onto the forklift through inserting both forks into the fork pockets. The rear of the jib crane then seats against the back of the fork and a security chain wraps the forklift carriage to hold it into position.

Load Capacity for the Jib Boom Forklift Attachment

The load capacity of a forklift jib has a maximum of about 1935 pounds to as much as 6000 lbs on either the retracted or extended positions range. You may need to ask a material handling specialist regarding the particular restrictions of your forklift application. The load capacity rankings are used for the jib itself and not the forklift or even the maximum load which can be transferred securely using a certain lift truck. It is very important remember that each time whichever attachments such as a lift truck jib are fitted to the forklift, the new center of gravity made by the accessory would reduce the overall lift capability of the forklift. There are instructions available that offer information on how to properly gauge these load limits.

Fork Trucks & Fork lift Attachment Safe Usage

Prior to utilizing whatever forklift jib, be sure that the hooks and shackles are correctly secured to the forklift. Verify and even double check that the pins are tight. It is very important that the load calculations have been correctly made and double checked. Keep in mind to take into consideration the fact that rated capacities sometimes lessen whenever the boom is in a raised position, whenever the boom is fully extended with telehandlers or when the mast is tilted forward.

Several vital suggestions about the modifiable jib are: never pull a load utilizing a lift truck jib accessory, since these kinds of accessories are meant for vertical lift only. At all times pick up the load without letting it sway. Use extreme caution every time a load is lifted so as to prevent tipping over the truck.